MS150913.1

LISTING OF THE CLAIMS

This listing of claims will replace all other versions of claims in the application.

- 1. (Original): A data compression system, comprising:
 - a scanning component which scans at least a portion of a transformed image, wherein the scan is performed substantially in a horizontal direction on a first section of the portion and in a vertical direction on a second section of the portion to enable improved data compression of the transformed image.
- 2. (Original): The data compression system of claim 1, wherein the horizontal and vertical scan directions are performed via a contiguous scan of the respective sections to enable improved data compression of the transformed image.
- 3. (Original): The data compression system of claim 1, further comprising a wavelet transform subsystem for transforming an image into wavelet coefficients via low pass and high pass filters applied to the image.
- (Original): The data compression system of claim 3, further comprising a
 quantizer for reducing stored data associated with the wavelet coefficients.
- Original): The data compression system of claim 3, further comprising a reordering and blocking subsystem to provide a matrix of wavelet coefficients that are organized into at least one of low-low (LL), low-high (LH), high-low (HL), and high-high (HH) sub-bands.
- 6. (Original): The data compression system of claim 5, wherein the LH sub-bands are scanned in the vertical direction and the HL sub-bands are scanned in the horizontal direction.

- (Original): The data compression system of claim 5, wherein the LL and HH subbands are scanned in either the horizontal or the vertical direction.
- (Original): The data compression system of claim 5, wherein run length encoding is employed to encode the scanned coefficients.
- (Original): The data compression system of claim 8, wherein at least one of Golomb-Rice encoding and Arithmetic encoding is employed to encode the scanned coefficients.
- 10. (Original): A method for providing a data compression system, comprising:

 scanning at least a portion of a transformed image in substantially a
 horizontal direction on a first section of the portion; and

 scanning in a vertical direction on a second section of the portion of the
 transformed image to enable improved data compression of the transformed
 image.
- (Original): The method of claim 10, wherein the horizontal and vertical scan directions are performed via a contiguous scan of the respective sections to enable improved data compression of the transformed image.
- 12. (Original): The method of claim 10, further comprising: transforming an image into wavelet coefficients via low pass and high pass filters applied to the image.
- 13. (Original): The method of claim 12, further comprising:

 reordering and blocking to provide a matrix of wavelet coefficients that
 are organized into at least one of low-low (LL), low-high (LH), high-low (HL),
 and high-high (HH) sub-bands.

- 14. (Original): The method of claim 13, wherein the LH sub-bands are scanned in the vertical direction and the HL sub-bands are scanned in the horizontal direction.
- 15. (Original): The method of claim 13, wherein the LL and HH sub-bands are scanned in either the horizontal or the vertical direction.
- 16. (Original): A data compression system, comprising: means for scanning at least a portion of a transformed image in substantially a horizontal direction on a first section of the portion; and means for scanning in a vertical direction on a second section of the portion of the transformed image to enable improved data compression of the transformed image.
- 17. (Original): The data compression system of claim 16, wherein the horizontal and vertical scan directions are performed *via* a contiguous scan of the respective sections to enable improved data compression of the transformed image.
- 18. (Original): The data compression system of claim 16, further comprising: means for transforming an image into wavelet coefficients via low pass and high pass filters applied to the image.
- 19. (Original): The data compression system of claim 18, further comprising: means for reordering and blocking to provide a matrix of wavelet coefficients that are organized into at least one of low-low (LL), low-high (LH), high-low (HL), and high-high (HH) sub-bands.
- 20. (Original): The data compression system of claim 19, wherein the LH sub-bands are scanned in the vertical direction and the HL sub-bands are scanned in the horizontal direction.

MS150913.1

- 21. (Original): The data compression system of claim 19, wherein the LL and HH sub-bands are scanned in either the horizontal or the vertical direction.
- 22. (Original): An image compression system, comprising:
 - a wavelet transform subsystem for transforming an image into wavelet coefficients; and

a scanning component which contiguously scans at least a portion of the transformed image, wherein the contiguous scan is performed substantially in a horizontal direction on a first section of the portion and in a vertical direction on a second section of the portion to enable improved data compression of the transformed image.